MERV RATING CHART

Standard 52.5 Minimum Efficiency Reporting	Dust Spot		Typical Controlled	Typical Applications and	
Value	Efficiency	Arrestance	Contaminant	Limitations	Typical Air Filter/Cleaner Type
20	n/a	n/a	< 0.20 nm norticle size	Cleanrooms	<u>≥</u> 99.999% eff. On .1020 pm
19	n/a	n/a	< 0.30 pm particle size Virus (unattached)	Radioactive Materials	Particles Particles
18	n/a	n/a	Carbon Dust	Pharmaceutical Man.	Particulates
10	n/a	n/a	All Combustion smoke	Carcinogenetic Materials	>99.97% eff. On .30 pm Particles
16	n/a	n/a	.30-1.0 pm Particle Size	General Surgery	Bag Filter- Nonsupported
15	>95%	n/a	All Bacteria	Hospital Inpatient Care	microfine fiberglass or
14	90-95%	>98%	Most Tobacco Smoke	Smoking Lounges	synthetic media, 12-36 in. deep, 6- 12 pockets Box Filter- Rigid Style Cartridge Filters 6 to 12" deep m ay use
13	89-90%	>98%	Proplet Nuceli (Sneeze)	Superior Commercial Buildings	lofted or paper media.
12	70-75%	>95%	1.0-3.0 pm Particle Size	Superior Residential	Bag Filter- Nonsupported
11	60-65%	>95%	Legionella Humidifier Dust Lead Dust	Better Commercial Buildings	microfine fiberglass or synthetic media, 12-36 in. deep, 6- 12 pockets
10	50-55%	>95%	Milled Flour Auto Emissions	Hospital Laboratories	Box Filter - Rigid Style Cartridge Filters 6 to 12" deep m ay use lofted or paper media.
9	40-45%	>90%	Welding Fumes		
8	30-35%	>90%	3.0-10.0 pm Particle Size	Commercial Buildings	Pleated Filters- Disposable, extended surface area, thick with cotton-polyester blend media,
7	05.000/		Mold Spores		cardboard frame
7	25-30%	>90%	Hair Spray Fabric Protector	Better Residential	Cartridge Filters- Graded density viscous coated cube or pocket filters, synthetic media
6	<20%	85-90%	Dusting Aids	Industrial Workplace	
			Cement Dust		Throwaway- Disposable synthetic panel filter.
5	<20%	80-85%	Pudding Mix	Paint Booth Inlet	
4	<20%	75-80%	>10.0 pm Particle Size Pollen	Minimal Filtration	Throwaway- Disposable fiberglass or synthetic panel filter.
3	<20%	70-75%	Dust Mites Sanding Dust	Residential	Washable- Aluminum Mesh
2	<20%	65-70%	Spray Paint Dust		
1	<20%	<65%	Textile Fibers Carpet Fibers	Window A/C Units	Electrostatic- Self charging woven panel filter.
I	N20 %	NO3 70	Calper Finels		